


## **H306C Product Show**





## **Functions & Features**

- 1、Reasonable and reliable design, low noise, smooth operation and long service life;
- 2、With functions of anti-tail, anti-reverse pass and so on;
- 3、Card can be set "with memory" or "without memory" functions;
- 4. With automatic reset function, i.e. after having access to the gate, the gate automatically restores to the locked state if not pass within the time set;
- 5、With infrared anti-clip function (anti-clip when gate is open or running);
- 6. Compatible with IC, ID card, scanning and face recognition, etc.
- 7. Two modes of operation are available: open or closed.
- 8. Various working modes are available, including two-way card reading and one-way card reading, etc.

## Size drawing







Parame-	
Size (L*W*H)	1400*185*1020mm
Material	Top $\delta$ =1.5mm/ body $\delta$ =1.2mm SUS304
Filling Panel material	8mm clear Acrylic
Arm material	10mm clear Acrylic
Pass width	600-900mm
Movement	Brushless Movement of Swing Gate
Power supply	24V 150W
Input voltage	AC100V~240V,50/60HZ
Drive Unit	DC brushless motor 60K 50W
Pass rate	35-50 persons/minute
Open Speed	0.5s/1.5s
Sensor	7 pairs
Indicator Light	RGB light
Control Unit	Brushless control system
Noise	≤65dB
Temperature	-20°C~+70°C
Humidity	≤90% No condensation
IP	IP4X
Environment	Indoor and outdoor (outdoor with canopy)



## Case share

