

Case E (395)



Waterproof casing for an Ajax hub with an internal battery. For outdoor and indoor use.



Flexibility for building reliable systems in different environments


Remote and off-grid sites. Paired with Hub BP Jeweller, Case E allows building autonomous security systems with backup batteries, even for locations where power infrastructure is unavailable.

Grade 3 installations in demanding environments. Used with Ajax Grade 3 certified hubs, Case E ensures compliance and protects equipment from dust, moisture, and impact, making it suitable for industrial facilities, logistics hubs, and challenging locations.



Quick installation and maintenance

- Tamper alarm on the lid opening or detachment from the surface
- Built-in bubble level for a perfectly accurate mounting position
- Multiple use even after dismantling and changing the device configuration
- Perforations for cable fixing and routing on the cases' sides



Compatible devices

Hubs¹

- Hub BP Jeweller (without casing)
- Ajax Superior Hub Hybrid (4G) (without casing)
- Ajax Superior Hub Hybrid 2 (without casing)
- Ajax Superior MegaHub (without casing)

Ajax batteries²


- Internal battery NB (7.2V/95Ah)
- Internal battery RB (6.4V/36Ah)
- Internal battery NB (7.2V/190Ah)
- Internal battery RB (6.4V/78Ah)

Compliance

EN 50131 (Grade 3)
PD 6662:2017

Compatibility

For detailed information, scan the QR code or follow the link:



ajax.systems/tools/devices-compatibility/?models=CS.E.Y

Installation

Operating temperature range
from –25 °C to +55 °C
from –13 °F to 131 °F

Operating humidity
up to 95%

Complete set

Case E (395)
2 × Module Holder (type A)
2 × Cable for connecting tamper board
Spirit level
Installation kit
Quick start guide

Casing

Color
white, black

Dimensions
395 × 300 × 108 mm
15.6" × 11.81" × 4.25"

Weight for the device in black
TBD

Weight for the device in white
TBD

Protection class
IP65

Impact protection
IK08

¹ To install Hub BP Jeweller (without casing), Module Holder (type A) holders are required. For other compatible hubs, Module Holder (type B) holders can be used .

² Case E (395) supports installation of third-party batteries. Battery size should be checked before installation.



For detailed information, scan the QR code or follow the link:
ajax.systems/support/devices/case-e-395/



support@ajax.systems



@AjaxSystemsSupport_Bot



ajax.systems