

EN54 Internal Battery (24h/72h)

Rechargeable Li-ion battery to install into EN54 Fire Hub Jeweller or EN54 Fire ReX Jeweller



Battery versions	Type	Voltage	Capacity	Battery life according to EN 54-4
EN54 Internal Battery (24h)	Rechargeable Li-ion battery	7.4 V	5 Ah	24 h
EN54 Internal Battery (72h)	Rechargeable Li-ion battery	7.4 V	10 Ah	72 h



Reliable power backup for compliant fire safety

Rechargeable internal batteries designed for EN54 Fire Hub Jeweller and EN54 Fire ReX Jeweller ensure system autonomous operation in the event of a power outage. The batteries guarantee the uninterrupted performance of Ajax fire protection systems in critical situations in accordance with the EN 54-4 standard.



Maintenance-free and safe to handle

- Ready to use out of the box
- Easily and quickly installed into EN54 Fire Hub Jeweller or EN54 Fire ReX Jeweller
- Effortlessly replaced using a dedicated tool

Enclosure		Power supply	Installation	
N54 Internal Battery (24h) EN54 Internal Battery (72h) Maximum load curren		Maximum load current	Operating temperature range	
Dimensions	Dimensions	3.2 A	from -10 °C to +40 °C	
166 × 87 × 23 mm	166 × 87 × 23 mm	End-of-life battery voltage	from 14 °F to 104 °F	
6.54" × 3.43" × 0.92"	6.54" × 3.43" × 0.92"	6 V==	Operating humidity	
Weight	Weight		up to 75% non-condensing	
270 g	443 g		Protection class	
9.52 oz	15.63 oz		IP20	
Compatibility with hubs and range extenders		Color	Complete set	
For detailed information, scan the QR code or follow the link:		black, white	Internal battery	
ajax.systems/tools models=IB.5424.Y,I	<u>/devices-compatibility/?</u> B.5472.Y			





support@ajax.systems







For detailed information, scan the QR code or follow the link: