Case C (260)

Casing for Ajax device and battery

Compatibility	Superior LineSupply Fibra with a battery up to 7 Ah
Device installation	Number of slots 1 To install a different number of devices, select a model with the appropriate number of slots: • Case A (106); • Case B (175); • Case D (430).
	Plastic rails to secure a module Slide LineSupply Fibra along the rails to remove it from the casing.
	Cable fasteners to hold the cables together with ties
	Plastic stoppers to protect the installed device During drilling, the instrument rests on the Case stoppers.
	Bubble level To check the inclination angle of the casing during installation.
	Recesses for drilling Ø20 mm or Ø32 mm The drill bit is fixed in the recess and does not move during drilling. We recommend using a hole saw for plastic.
	Wider holes To ensure that the casing is installed correctly, even if there are errors during installation.
	Holders for a battery up to 7 Ah To prevent accidental dislodgement of the battery.

Key features	Tamper board Included in the Case complete set. The tamper board connects to the appropriate LineSupply Fibra connector and protects the installed device from sabotage. Holding screws in the casing lid Latches to secure the lid during installation The latches prevent the lid from falling off Case
	until it is secured with screws.
Recomendations	The device is designed for indoor use only. Case is produced in several versions.
Product	Dimensions 260 × 195 × 93 mm 10.24" × 7.68" × 3.66" Weight of the black Case 997 g 2.2 lb Weight of the white Case 1,045 g 2.3 lb Operating temperature range from -10 °C to +40 °C from 14 °F to 104 °F Operating humidity up to 75% Protection class IP20
Colours	Black White
Complete set	Case C (260) Tamper board Installation kit Quick start guide
Warranty	24 months