

Case D (430)

Casing for Ajax devices and batteries

Compatibility	<p>Superior LineSplit Fibra Superior LineProtect Fibra Superior MultiRelay Fibra Superior LineSupply Fibra With batteries up to 18 Ah. Hub Hybrid (2G) Hub Hybrid (4G) With battery up to 9 Ah. Installing the hub in Case D (430) does not meet the Grade (EN 50131) requirements. The compliant version will be available soon.</p>
Devices installation	<p>Number of devices up to 8 To install a different number of devices, select a model with the appropriate number of slots:</p> <ul style="list-style-type: none">• Case A (106);• Case B (175);• Case C (260). <p>Plastic holders Module Holder (type A) Place the required number of Module Holder (type A) into the casing to accommodate Superior LineSplit Fibra, Superior LineProtect Fibra, and Superior MultiRelay Fibra modules. The Case D (430) complete set includes a total of 4 holders. If you need more, additional holders can be purchased separately.</p> <p>Module Holder (type B) Place two Module Holder (type B) into the casing to accommodate the Hub Hybrid board. Holders are sold separately.</p> <p>Plastic rails to secure LineSupply Fibra Slide LineSupply Fibra along the rails to remove it from the casing. No holders are required to secure the module.</p> <p>Cable fasteners to hold the cables together with ties</p> <p>Bubble level To check the inclination angle of the casing during installation.</p> <p>Recesses for drilling Ø32 mm, Ø40 mm, or Ø63 mm</p>

	<p>The drill bit is fixed in the recess and does not move during drilling. We recommend using a hole saw for plastic.</p> <p>Wider holes To ensure that the casing is installed correctly, even if there are errors during installation.</p> <p>Holders for batteries up to 18 Ah At the bottom of the casing.</p> <p>Holding stripe for the battery To prevent accidental dislodgement of the battery.</p>
Key features	<p>Tamper board Included in the Case complete set. The tamper board connects to the appropriate connector of one of the devices and protects the installed devices from sabotage.</p> <p>Device rotation by 180° The devices in the casing can be rotated by 180°, providing two fixation options.</p> <p>Holding screws in the casing lid</p> <p>Latches to secure the lid during installation The latches prevent the lid from falling off Case until it is secured with screws.</p>
Recommendations	<p>The device is designed for indoor use only. Case is produced in several versions.</p>
Product	<p>Dimensions 430 × 400 × 133 mm 16.93" × 15.75" × 5.24"</p> <p>Weight of the black Case 3,343 g 7.37 lb</p> <p>Weight of the white Case 3,381 g 7.45 lb</p> <p>Operating temperature range from -10 °C to +40 °C from 14 °F to 104 °F</p>

	Operating humidity up to 75%
Colours	Black White
Complete set	Case D (430) Tamper board Holding stripe for a battery Holder — 4 pcs. Installation kit Quick start guide
Warranty	24 months