

Superior StreetSiren DoubleDeck Fibra

Wired acoustic LED siren with a clip lock for a branded faceplate

Compatibility	Compatible hub models <ul style="list-style-type: none">• Hub Hybrid (2G)• Hub Hybrid (4G)
Communication	Fibra communication technology <p>Proprietary wired communication technology. Fibra combines the reliability of wires with the freedom of radio connection.</p> It features: <ul style="list-style-type: none">• Two-way communication.• Advanced anti-sabotage.• Instant notifications.• Remote configuration via the Ajax apps. Line connection <p>4-core cable</p> Fibra line length <p>up to 2,000 m / up to 6,600 ft <i>When using the U/UTP cat.5 twisted pair.</i></p> <p>Calculate the line length at the facility</p> Encrypted communication
Key features	Alarm type <p>acoustic and LED <i>Buzzer and LED frame.</i></p> Alarm volume <p>from 85 to 113 dB at a distance of 1 m / 3.3 ft <i>Adjusted by PRO or user with admin rights in the Ajax app.</i></p> Alarm duration

	<p>from 3 s to 3 min <i>Adjusted by PRO or user with admin rights in the Ajax app.</i></p> <p>Siren sound frequency 3.5 ± 0.5 kHz</p> <p>Chime The siren makes a special sound to notify that the opening detectors are triggered when the system is disarmed.</p> <p>Events indication</p> <ul style="list-style-type: none"> • Alerts. • Entry/exit delays. • Security mode. • Security mode changing. • After-alarm indication.
<p>The siren is designed for indoor and outdoor use. Recommended installation height is 2.5 m/8.2 ft and higher.</p>	
Customized branded faceplate	<p>Brandplate Security service providers can print their logo and contact information on the siren's front panel.</p> <p>Brandplate is sold separately from street sirens. To place an order, reach out to your regional Ajax partner. You can also compose a faceplate design in the Brandplate constructor.</p>
Anti-sabotage protection	<p>Tampering alarm Sends notification if anyone tries to detach the siren from its surface or remove the device from the mounting panel.</p> <p>Protection against forgery Device authentication</p>
Power supply	<p>Fibra line power supply 7–30 V$\overline{=}$, up to 1.2 W <i>The siren is powered by the control panel.</i></p>
Enclosure	<p>Dimensions 198.5 × 198.5 × 59 mm / 7.81" × 7.81" × 2.32"</p>

	<p>Weight 516 g / 18.20 oz</p> <p>Operating temperature range from -25°C to +60°C / from -13°F to 140°F</p> <p>Operating humidity up to 95%</p> <p>Protection class IP54</p>
Colours	<ul style="list-style-type: none"> • Black • White
Complete set	<p>Superior StreetSiren DoubleDeck Fibra SmartBracket mounting panel Installation kit Quick Start Guide</p>
Additional information	<p>Compliance with standards Learn more</p> <p>Warranty 24 months Learn more</p> <p>User manual Learn more</p>